


Kinghelm®

REV. NUMBER		DESCRIPTION		DWN	CHK	DATE
A		DESIGN				



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
④	套管	黑色热缩套管, OD:2.0MM	AS
③	端子	高仿I-PEX, 1.13端子, 镀金	1
②	接头	SMA母头内针, 分体, 11牙, 镀金	1
①	同轴线	RF 1.13灰色线, OD:1.13mm	AS

金航标电子有限公司

- NOTES:
- ELECTRICAL:
 - VOLTAGE RATING:DCV 300V 10MS
 - CONDUCTANCE RESISTANCE:3.0 OHM/MAX.
 - INSULATION RESISTANCE: 5.0M OHM/MIN.
 - THE CABLE SHOULD BE 100% ELECTRICAL TEST
 - IT SHOULD BE NO ANY OPENS/SHORT, MISWIRING AND INTERMITTENT FAILURES
 - MATERIAL:
 - SEE TABLE
 - MECHANICAL:
 - SMA PULL FORCE: 12.0KGS.
 - ALL COMPONENTS ARE ROHS COMPLIANT.

ALL DIMENSION ARE IN MM		DRAWN	DATE	TITLE	
COMPUTER GENERATED IN SOLIDWORKS		Janny	2018/05/04	RF CABLE	
DO NOT SCALE THIS DRAWING		ENG.		I-PEX 1.13 TO SMA / F L=200 MM	
PROJECTION		MFG.		SIZE	Number
GENERAL TOLERANCE FOR ANGLES ± 1° ± 0.3 ± 0.25 ± 0.150		Q.A.		B	A

CUSTOMER P/N: