




Features

- Low Turn-on Voltage
- Fast switching
- PN junction guard ring for transient and ESD protection


| DEVICE | MARKING | | TYPE |
|--------|---------|-----|--------|
| | 1 | 2 | |
| BAT54 | KL1 | L4 | Single |
| BAT54A | KL2 | L42 | Dual |
| BAT54C | KL3 | L43 | Dual |
| BAT54S | KL4 | L44 | Dual |




| SOT-23 | | |
|----------------------|-------|-------|
| Dim | Min | Max |
| A | 0.37 | 0.51 |
| B | 1.20 | 1.40 |
| C | 2.30 | 2.50 |
| D | 0.89 | 1.03 |
| E | 0.45 | 0.60 |
| G | 1.78 | 2.05 |
| H | 2.80 | 3.00 |
| J | 0.013 | 0.10 |
| K | 0.903 | 1.10 |
| L | 0.45 | 0.61 |
| M | 0.085 | 0.180 |
| α | 0° | 8° |
| All Dimensions in mm | | |

Maximum Ratings @ $T_A = 25^\circ\text{C}$ unless otherwise specified


| Parameter | Symbol | Limit | Unit |
|--|-----------------|---------------|--------------------|
| Repetitive peak reverse voltage | V_{RRM} | 30 | V |
| Average rectified forward current | $I_{F(AV)}$ | 200 | mA |
| Repetitive Peak Forward Current | I_{FRM} | 300 | mA |
| Repetitive peak forward surge current at Pulse width=1 second | I_{FSM} | 600 | mA |
| Power dissipation | P_{tot} | 290 | mW |
| Thermal resistance junction to ambient air | $R_{\theta JA}$ | 430 | $^\circ\text{C/W}$ |
| Junction temperature | T_j | 150 | $^\circ\text{C}$ |
| Storage temperature range | T_{stg} | - 55 to + 150 | $^\circ\text{C}$ |




BAT54



BAT54A



BAT54C







BAT54S

Electrical Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified

| Parameter | Symbol | Min. | Max. | Unit |
|---|-----------|-----------------------|---------------------------------|---------------|
| Forward voltage at $I_F = 0.1\text{ mA}$ at $I_F = 1\text{ mA}$ at $I_F = 10\text{ mA}$ at $I_F = 30\text{ mA}$ at $I_F = 100\text{ mA}$ | V_F | - - - - - | 240 320 400 500 800 | mV |
| Reverse current at $V_R = 25\text{ V}$ | I_R | - | 2 | μA |
| Breakdown voltage at $I_R = 10\text{ }\mu\text{A}$ | V_R | 30 | - | V |
| Total capacitance at $V_R = 1\text{ V}$, $f = 1\text{ MHz}$ | C_{tot} | - | 10 | pF |
| Reverse recovery time at $I_F = 10\text{ mA}$, $I_R = 10\text{ mA}$, $I_{RR} = 1\text{ mA}$, $R_L = 100\text{ }\Omega$ | t_{rr} | - | 5 | ns |

TYPICAL TRANSIENT CHARACTERISTICS



IMPORTANT NOTICE

HC-SEMI reserves the right to make changes without further notice to any products herein.

HC-SEMI makes no warranty, representation or guarantee regarding

The suitability of its products for any particular purpose, nor does HC-SEMI assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages.

“Typical” parameters can and do vary in different applications. All operating parameters, including “Typicals” must be validated for each customer application by customer’s technical experts.

HC-SEMI products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the HC-SEMI product could create a situation where personal injury or death may occur.

Should Buyer purchase or use HC-SEMI products for any such unintended or unauthorized application, Buyer shall indemnify and hold HC-SEMI and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that HC-SEMI was negligent regarding the design or manufacture of the part.