



**ATTENTION**  
OBSERVE PRECAUTIONS  
FOR HANDLING  
ELECTROSTATIC  
SENSITIVE  
DEVICES



**CAUTION**

This bag contains

MOISTURE-SENSITIVE DEVICES

LEVEL  
**3**

If Blank, see adjacent  
bar code label

1. Calculated shelf life in sealed bag: 12 months at  $< 40^{\circ}\text{C}$  and  $< 90\%$  relative humidity (RH)
2. Peak package body temperature:  $260^{\circ}\text{C}$   
If blank, see adjacent bar code label
3. After bag is opened, devices that will be subjected to reflow solder or other high temperature process must  
a) Mounted within:  $168$  hours of factory  
If blank, see adjacent bar code label  
conditions  $\leq 30^{\circ}\text{C}/60\%$   
b) Stored at  $\leq 30^{\circ}\text{C}/60\%$
4. Devices require bake, before mounting, if:  
a) Humidity Indicator Card is  $> 10\%$  when read at  $23 \pm 5^{\circ}\text{C}$   
b) 3a or 3b not met
5. If baking is required, devices may be baked for 48 hours at  $125 \pm 5^{\circ}\text{C}$   
Note: If device containers cannot be subjected to high temperature or shorter bake times are desired,  
reference IPC/JEDEC J-STD-033 for bake procedure

Bag Seal Date: \_\_\_\_\_

If blank, see adjacent bar code label

Note: Level and body temperature defined by IPC/JEDEC J-STD-020



平芯微®

Wuxi PWCHIP Semi Technology CO., LTD

Product: PW2051

Lot No: \_\_\_\_\_

D/C: 2350

Date:

2023/12/06

QTY: 3000

无锡市平芯微半导体科技有限公司

www.pwchip.com

ROHS



夸克微科技

夸克微科技

夸克微科技