



PRODUCT DATA SHEET

To learn more about JGSEMI, please visit our website at



Datasheet



Resources





Samples

Please note: Please check the JINGAO Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.jg-semi.cn. Please email any questions regarding the system integration to JINGAO_questions@jgsemi.com.

FEATURES

- Power MOSFET: 1.8-V Rated
- Gate-Source ESD Protected
- High-Side Switching
- Low On-Resistance: 0.4Ω
- Low Threshold: 0.8 V (typ)
- Fast Switching Speed: 10 ns
- We declare that the material of product complies with RoHS requirements and Halogen Free.
- S- prefix for automotive and other applications requiring unique site and control change requirements; AEC-Q101 qualified and PPAP capable.



BENEFITS

- Ease in Driving Switches
- Low Offset (Error) Voltage
- Low-Voltage Operation
- High-Speed Circuits
- Low Battery Voltage Operation

APPLICATIONS

- Drivers: Relays, Solenoids, Lamps, Hammers, Displays, Memories.
- Battery Operated Systems
- Power Supply Converter Circuits
- Load/Power Switching Cell Phones, Pagers

MAXIMUM RATINGS(Ta = 25℃)

Parameter		Symbol	5 secs	Steady State	Unit
Drain-Source Voltage		VDS	20		V
Gate-Source Voltage		VGS	±8		V
Continuous Drain Current (TJ = 150℃) (Note 2)	TA = 25℃	ID	600	500	mA
	TA = 85℃		400	350	
Pulsed Drain Current(Note 1)		IDM	1000		
Continuous Source Current (diode conduction)(Note 2)		IS	275	250	
Maximum Power Dissipation(Note 2)		PD		250	mW
Thermal Resistance, Junction to Ambient		RθJA		500	℃/W
Operating Junction and Storage Temperature Range		TJ , Tstg	-55 ~+150		℃

1.Pulse width limited by maximum junction temperature.

2.Surface Mounted on FR4 Board.

ELECTRICAL CHARACTERISTICS (Ta= 25°C)
Static





Characteristic	Symbol	Min.	Typ.	Max.	Unit
Gate Threshold Voltage (VDS = VGS , ID = 250μA)	VGS(th)	0.35	-	1.0	V
Gate-Body Leakage (VDS = 0 V, VGS = ±4.5 V)	IGSS	-	±0.5	±1	μA
Zero Gate Voltage Drain Current (VDS = 20 V, VGS = 0 V) (VDS = 20 V, VGS = 0 V, TJ = 85°C)	IDSS	- -	0.3 -	100 5	nA μA
On-State Drain Current(Note 1) (VDS = 5 V, VGS = 4.5 V)	ID(on)	700	-	-	mA
Drain-Source On-State Resistance(Note 1) (VGS = 4.5 V, ID = 500 mA) (VGS = 2.5 V, ID = 500 mA) (VGS = 1.8 V, ID = 350 mA)	RDS(on)		0.25 0.3 0.5	0.4 0.5 0.7	Ω
Forward Transconductance(Note 1) (VDS = 10 V, ID = 400 mA)	gfs		1		S
Diode Forward Voltage(Note 1) (IS = 150 mA, VGS = 0 V)	VSD		0.8	1.2	V





Dynamic(Note 2)

Total Gate Charge	(VDS = 10 V, VGS = 4.5 V, ID = 250 mA)	Qg		750		pC
Gate-Source Charge		Qgs		75		
Gate-Drain Charge		Qgd		225		
Turn-On Delay Time	(VDD = 10 V, RL = 47Ω, ID=200 mA, VGEN = 4.5 V, RG = 10Ω)	td(on)		5		ns
Rise Time		tr		5		
Turn-Off Delay Time		td(off)		25		
Fall Time		tf		11		


3.Pulse test; pulse width ≤300 μs, duty cycle ≤ 2%.

4.Guaranteed by design, not subject to production testing.


ELECTRICAL CHARACTERISTICS CURVES





OUTLINE AND DIMENSIONS



SOT883			
DIM	MIN	TYP	MAX
D	0.95	1.00	1.05
E	0.55	0.60	0.65
e	-	0.64	-
e1	-	0.34	-
L	0.19	0.24	0.29
L1	0.22	0.27	0.32
b	0.10	0.15	0.20
b1	0.44	0.49	0.54
A	0.43	0.48	0.53
A1	0	-	0.05
All Dimensions in mm			



SOLDERING FOOTPRINT



Dimensions	(mm)
c	0.70
X	1.10
X1	0.40
X2	0.40
Y	0.20
Y1	0.55

Attention

1, Any and all JGSEMI products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical or material damage. Consult with your JGSEMI representative nearest you before using any JGSEMI products described or contained herein in such applications.

2, JGSEMI assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all JGSEMI products described or contained herein.

3, Specifications of any and all JGSEMI products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.

4, In the event that any or all JGSEMI products (including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.

5, No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of JGSEMI Semiconductor CO., LTD.

6, Any and all information described or contained herein are subject to change without notice due to product technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the JGSEMI product that you intend to use.